## AMENDMENTS TO THE CLAIMS:

Kindly cancel claims 11 and 23, without prejudice, and amend claims 1, 3, 12, 14 and 20, as shown below.

This listing of claims will replace all prior versions and listings of claims in the Application:

Claim 1 (currently amended): A data transmitter characterized by comprising:

a transmission line which connects to the input/output circuits of said integrated circuits and has an element that changes an effective reactance per unit length depending on at least one of a signal voltage and a signal current, wherein said transmission line is formed at least in or on a printed eireuitwiring board[[.]], and

a plurality of integrated circuits each having at least one input/output circuit; and

wherein a maximum value of a change component in the effective reactance per unit length that changes depending on at least one of the signal voltage and the signal current in said transmission line is not smaller than a value of a fixed component independent of the signal voltage and the signal current.

Claim 2 (cancelled).

Claim 3 (currently amended): A data transmitter according to claim 1, characterized in that said integrated circuits and said transmission line are formed on a singlethe printed wiring board[[,]], and the printed wiring board is a single printed wiring board.

Claim 4 (previously presented): A data transmitter according to claim 1, characterized in that said transmission line comprises a grounded ground conductor, a signal conductor which receives said signal voltage between the ground conductor and the signal conductor, and an

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE, SUITE 140 TUCSON, AZ 85718 TEL, 520.882.7623 FAX. 520.882.7643

insulating material which contains the element and insulates the signal conductor and the ground conductor from each other.

Claim 5 (original): A data transmitter according to claim 4, characterized in that the element includes one of a dielectric and a magnetic substance.

Claim 6 (original): A data transmitter according to claim 5, characterized in that the dielectric exhibits a nonlinear relationship between an electric field and dielectric polarization generated in the dielectric.

Claim 7 (original): A data transmitter according to claim 6, characterized in that the dielectric is at least one of lead zirconate titanate, bismuth strontium tantalate, ferroelectric, and liquid crystal.

Claim 8 (original): A data transmitter according to claim 5, characterized in that the magnetic substance exhibits a nonlinear relationship between a magnetic field and magnetization generated in the magnetic substance.

Claim 9 (original): A data transmitter according to claim 8, characterized in that the magnetic substance is at least one of NiZn ferrite and sendust.

Claims 10-11 (cancelled).

Claim 12 (currently amended): A data transmission line characterized by comprising:

said data transmission line connecting [[the]] input/output circuits of a plurality of
integrated circuits:

an element which changes an effective reactance per unit length depending on at least one of a signal voltage and a signal current;

a grounded ground conductor;

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE, SUITE 140

TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

a signal conductor which receives said signal voltage between said ground conductor and said signal conductor; and

an insulating material which contains the element and insulates said signal conductor and said ground conductor from each other, wherein said ground conductor is formed at least in or on a printed wiring board, said insulating material is arranged in the printed wiring board, and [[said]]said signal eonduct or conductor is arranged in said insulating material[[.]], and

wherein a maximum value of a change component in the effective reactance per unit length that changes depending on at least one of the signal voltage and the signal current is not smaller than a value of a fixed component independent of the signal voltage and the signal current.

Claim 13 (cancelled).

Claim 14 (currently amended): A data transmission line according to claim [[2]]12, characterized in that the element includes one of a dielectric and a magnetic substance.

Claim 15 (original): A data transmission line according to claim 14, characterized in that the dielectric exhibits a nonlinear relationship between an electric field and dielectric polarization generated in the dielectric.

Claim 16 (original): A data transmission line according to claim 15, characterized in that the dielectric is at least one of lead zirconate titanate, bismuth strontium tantalate, ferroelectric, and liquid crystal.

Claim 17 (original): A data transmission line according to claim 14, characterized in that the magnetic substance exhibits a nonlinear relationship between a magnetic field and magnetization generated in the magnetic substance.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE, SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882,7643

Claim 18 (original): A data transmission line according to claim 17, characterized in that the magnetic substance is at least one of NiZn ferrite and sendust.

Claim 19 (caneelled).

Claim 20 (currently amended): A data transmission line characterized by comprising:

said data transmission line connecting [[the]] input/output circuits of a plurality of integrated circuits;

an element which changes an effective reactance per unit length depending on at least one of a signal voltage and a signal current;

a grounded ground conductor;

a signal conductor which receives said signal voltage between said ground conductor and said signal conductor; and

an insulating material which contains the element and insulates said signal conductor and said ground conductor from each other[[.]],

wherein said ground conductor and said signal conductor are formed apart from each other on a printed wiring board, and said insulating material is arranged between said ground conductor and said signal conductor on the printed wiring board and joined to said ground conductor and said signal conductor[[.]], and

wherein a maximum value of a change component in the effective reactance per unit length that changes depending on at least one of the signal voltage and the signal current is not smaller than a value of a fixed component independent of the signal voltage and the signal current.

Claim 21 (original): A data transmission line according to claim 12, characterized in that a plurality of data transmission lines are parallel-arrayed.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE, SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

175 CANAL STREET MANCHESTER, NH 03101 TEL. 603.668.1400

Claims 22-25 (cancelled).

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE, SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643